

- Demolition & Sorting Grabs
- Polyp Grabs
- Pulverisers
- Shears
- Hammer
- Multi-Quick Processors

## Demarec hamers



Type	DBC-10	DBC-20	DBC-30	DBC-40	DBC-45	DBC-65	DBC-85	DBC-120
Gewicht basismachine*	1,5-3 ton	2-6 ton	3-7 ton	4-10 ton	4-10 ton	7- 13 ton	9-15 ton	14-20 ton
Gewicht**	110 kg	250 kg	310 kg	460 kg	550 kg	650 kg	950 kg	1200 kg
Werkhoogte	1030 mm	1270 mm	1430 mm	1590 mm	1535 mm	1838 mm	1911 mm	2256 mm
Beitel diameter	48 mm	68 mm	70 mm	80 mm	85 mm	95 mm	100 mm	110 mm
Slagenergie (Joule)	190	450	840	980	1060	1450	1760	1880
Slagfrequentie (bpm)	1000-1500	450-1000	390-1000	450-100	500-900	350-700	390-700	400-700

### Hydrauliek

Werkdruk	90 bar	100 bar	105-155 bar	100-140 bar	135 bar	135 bar	135 bar	135 bar
Oliedebiet	15-35	30-60	45-70	55-100	50-100	60-120	70-130	70-130

Type	DBC-150	DBC-170	DBC-210	DBC-250	DBC-275	DBC-360	DBC-500	DBC-700
Gewicht basismachine*	18-26 ton	22-29 ton	25-32 ton	29-40 ton	33-50 ton	40-70 ton	45-70 ton	60-100 ton
Gewicht**	1600 kg	1870 kg	2200 kg	2520 kg	2950 kg	3750 kg	4750 kg	6950 kg
Werkhoogte	2473 mm	2500 mm	2730 mm	2912 mm	3050 mm	3215 mm	3430 mm	3866 mm
Beitel diameter	120 mm	130 mm	140 mm	150 mm	160 mm	170 mm	190 mm	210 mm
Slagenergie (Joule)	2880	3300	4500	5610	6000	8000	9800	13000
Slagfrequentie (bpm)	360-650	350-550	350-550	330-525	320-520	320-510	300-420	285-400

### Hydrauliek

Werkdruk	135 bar	135 bar	140 bar	140 bar	140 bar	140 bar	140 bar	150 bar
Oliedebiet	100-180	120-180	160-230	180-250	170-300	200-300	250-340	300-400

\* Gewichten ter indicatie. \*\* Gewicht excl. kopplaat.

Technische specificaties kunnen zonder bericht vooraf gewijzigd worden.